EUROPEAN PATENT OFFICE

Patent Abstracts of Japan

PUBLICATION NUMBER

56024024

PUBLICATION DATE

07-03-81

APPLICATION DATE

01-08-79

APPLICATION NUMBER

54097204

APPLICANT:

BABCOCK HITACHI KK;

INVENTOR

HISHINUMA TAKAO;


INT.CL.

B01D 53/34 B01D 53/02 C01B 17/04

TITLE

REMOVAL OF SULFUR DIOXIDE IN

EXHAUST GAS



ABSTRACT:

PURPOSE: To save heat energy and to reduce an amount of a cooling water for condensing S by a method wherein an adsorbing agent after SO₂ adsorption is heated at a specific temp. and S vapor with a specific temp. generated when desorbed SO₂ is reduced is utilized as a heat source for SO₂ desorption.

CONSTITUTION: SO_2 in an exhaust gas is adsorbed by an adsorbing agent 4 comprising activated coal or semi-code until near saturated point thereof and above described adsorbing agent 4 is continuously taken out to a desorbing device 2 and heated to $300\text{--}400^{\circ}\text{C}$ by a converting gas 14 with $800\text{--}900^{\circ}\text{C}$ supplied to an external heating portion 6 to discharge adsorbed SO_2 as a concentrated gas 13 and this gas i introduced to a S converter 3. The converter 3 packed with semi-coke 16 or the like is heated to $800\text{--}900^{\circ}\text{C}$ by a fuel 20 and the SO_2 gas 13 is reduced and converted to S vapor, thereafter the converted gas 14 with a temp. of $800\text{--}900^{\circ}\text{C}$ is supplied to the aforementioned heating portion 6. As a result, S vapor is cooled by heat exchanging with the adsorbing agent 4 and an amount of a cooling water in a condenser 17 is reduced as well as a heat source at the desportion tower 2 is economized.

COPYRIGHT: (C)1981, JPO& Japio